



SCHLAGE

3300U/3600U Series

Electromagnetic Locks



3300U/3600U Series Electromagnetic Locks

Schlage introduces the integrators an answer to the practical needs for electromagnetic locks. These compact electromagnetic locks are easy to stock, easy to select and easy to install. Schlage 3300U family consists of the 3600U with 1200 lbs of holding force, and the 3300U with 600 lbs of holding force. The variety and flexibility of Schlage 3300U family electromagnetic locks can meet your demands for high security, traffic control, or narrow line applications throughout your facility.

All models are ideal for open architecture and easily interface with electronic access control systems, automatic door operators, and fire or other hazard sensing systems for egress and emergency egress.

Benefits of Using 3300U/3600U Series Electromagnetic Locks

- Field selectable 12 or 24 VDC operation
- Simplified armature installation
- Variety of installation brackets available to adapt all kinds of environments
- Double magnet available with 3300U and 3600U series
- UL294 and UL10C certification
- 500,000 times life-cycle

3300U/3600U Series Electronmanetic Locks

How to order 3300U Series

3300U – DSM – MBS – L1 – RTD

Select Model _____

Select Options/Accessories _____

1. Select Model

3300U	Traffic Control, Single lock
3302U	Traffic Control, Double lock
3600U	High Security, Sing lelock
3602U	High Security, Double lock

2. Select Options/Accessories

DSM/DSM2	Door Status Monitor
MBS-L1	Magnetic Bond Sensor, with LED indicator for single door application
MBS-L2	Magnetic Bond Sensor, with LED indicator for double door application
RTD/RTD2	Relocking Time Delay
TJ****	Top Jamb for inswing door TJ3300 TJ3600
HDB****	Herculite Door Bracket HDB 3300**, 8mm/10mm/12mm available HDB 3600, 12mm available
HEB****	Header Extension Bracket HEB 3300 HEB 3600
AH****	Armature Holder, can be used for fire doors and glass doors AH 3300 200x55x15mm AH 3600 208x76x15mm
AB****	Angle Bracket AB 3300 AB 3600

**pls. specify the glass door thickness when order HDB

Specifications

3300U	
Holding Force	600 lbs.
Input Voltage	12/24VDC field selectable
Current Draw	0.5A@12VDC; 0.25A@24VDC
Dimension	Lock body 238x47.2x27.5mm Armature plate 185x38x12.5mm
Weight	4.63 lbs.
3302U	
Holding Force	600 lbs. per door leaf
Input Voltage	12/24VDC field selectable
Current Draw	1A@12VDC; 0.5A@24VDC
Dimension	Lock body 476x47.2x27.5mm Armature plate 185x38x12.5mm
Weight	9.26 lbs.
3600U	
Holding Force	1200 lbs.
Input Voltage	12/24VDC field selectable
Current Draw	0.5A@12VDC; 0.25A@24VDC
Dimension	Lock body 268x73x40mm Armature plate 185x61x16mm Armature plate w/DSM 252x61x16mm
Weight	10.75 lbs.
3602U	
Holding Force	1200 lbs. per door leaf
Input Voltage	12/24VDC field selectable
Current Draw	1A@12VDC; 0.5A@24VDC
Dimension	Lock body 536x73x40mm Armature plate 185x61x16mm Armature plate w/DSM 252x61x16mm
Weight	21.50 lbs.

About Allegion

Allegion (NYSE: ALLE) creates peace of mind by pioneering safety and security. As a provider of security solutions for homes and businesses, Allegion, a constituent of the S&P 500, employs more than 8,000 people and sells products in more than 120 countries across the world. Allegion comprises 27 global brands, including strategic brands CISA®, Interflex®, LCN®, Schlage®, and Von Duprin®.

For more, visit: www.allegion.com

